

ATEX EtherCAT Interface Module 4X60A

ATEX and IECEx certified (zone 1, 2, 21, 22) EtherCAT interface module for directly interfacing up to 4 digital ATEX / IECEx load cells via EtherCAT. The interface module type 4X60A can also be used in non-ATEX installations.

Type: 4160A, 4260A, 4360A, 4460A

Interface: EtherCAT

Special Features

Made in Denmark

EtherCAT interface

Weighing module for up to 4 digital load cells

For ATEX / IECEx and non-ATEX applications

Plug-and-play installation with Eilersen digital load cells

Advanced digital filters (configurable)

A "Digital Junction Box" that can be mounted near the load cells or in a central panel

Small Form Factor


Setup via dip switches

For ATEX / IECEx installation when supplied by power supply type 4051A

The power supply 4051A and module type 4X60A must be installed outside the hazardous zone

Application software can be made upon request

Dimensions (mm)



Specifications

Parameter	Unit	Data
Input		Up to 4 digital load cells
Output		EtherCAT
Non-ATEX: Standard Power Supply	Vdc	24Vdc \pm 5%, min. 2A
ATEX: Safe Power Supply	Vdc	ATEX certified Power Supply type 4051 A
Operating temperature range	$^{\circ}$ C	5 to 50
Weight	kg	0.5
Housing		Anodized Aluminium
Mounting		Mounting base or DIN rail

Options

Prepared for panel mounting on DIN rail

Mounted in stainless steel housing

Customized application software

OEM version

Copyright © 2025 Eilersen / [Cookie policy](#) / [Privacy policy](#) / [Disclaimer and Legal information](#)